

SEMIAUTOMATIC HINGED LANDING DOORS



NEW & EXISTING INSTALLATION
MODERNIZATIONS AND REPLACEMENT



RESIDENTIAL
LIFTS



Door configuration

LIFT APPLICATION

Door cycles per year:	Up to 350.000.
Traffic peak of the door:	Up to 240 cycles per hour.
Traffic lift speed:	Up to 2,5 m/s.

APPLICATION RANGE

Opening	Clear opening - CO (mm)	Clear height - CH (mm)
T1	500 - 1000 (Classic)	1500 - 2350
T1	500 - 1000 (Classic Blind)	1500 - 2350
T1	600 - 1000 (C310 "Luxury")	1100 - 2350
T1	600 - 1000 (C520 "Big vision")	800 - 2350
T1	600 - 1000 (C710)	2000
T1	600 - 1000 (M310 "Elegance")	1100 - 2350
T1	600 - 1350 (Classic heavy duty)	2000 - 2950

PANELS

Opening	Sheet metal	Small vision	Big vision	Aluminium glass	-
					-
x	✓	✓	✓	x	-

FRAMES DEFINITION

Frame depth (mm)	Jamb J1 (mm)	Header - HD (mm)	Jamb J2 (mm)	Remarks	Frame type				Option			
					STD	MSS MV	MSS MH	Con-cealed	Lateral covers	Without extra stroke	MRL	Without Lateral Punching
50	125	125	125	-	✓	x	x	x	x	x	x	x

STANDARDS

Opening	EN 81-1/2 Safety rules	EN 81-21 Existing buildings	EN 81-28 Remote alarm	EN 81-41 Impaired mobility	EN 81-71 Vandal resistance lifts		EN 81-72 Firefighters lifts	EN 81-20/50 Safety rules
					Cat. I	Cat. II		
T1	✓	✓	x	x	x	x	x	✓

☒ Available⁽¹⁾.
 ☐ Not available.
 ☐ Ask the commercial department.

⁽¹⁾Some option combinations may not be possible.

Door configuration

PROTECTION

Opening	IP20 Protection against a solid foreign body of 12,5 mm or more in diameter.	IP40 Protection against a solid foreign body of 1 mm or more in diameter.	IP54 Protection against dust and protected against water splashed from all directions.	IP67 Sealed against dust and protected against temporary water immersion (up to 1 meter for 30 sec)
T1	✓	✓	✓	✓

COMPATIBLE LOCKS

Manufactured by	Description	Lock options	Safety contact options
TI-Electrometal	Mechanic lock	IP20	IP20
Kronenberg	Mechanic lock	IP40 / IP54 / IP67	IP20 / IP67
	Electric lock	IP40 / IP54	IP20 / IP67
Schmersal	Mechanic lock	IP54	IP 54

COMPATIBILITY

Cam detail						
Case	Automatic horizontal sliding car door 40/10 PM, 50/11PM, 40/10 VF, 50/11 VF					Automatic folding car door G3, G5, G5-EM
Coupling	Sliding cams					Folding cams
Type of cam	Frontal retractable	Inverted lateral retractable	Lateral retractable	Fixed	Flexible Fixed	Lateral retractable
Toe guard type	Standard	Standard	Standard	Standard	Standard	Standard
Toe guard height	270	270	270	270	270	270
Thickness	2	2	2	2	2	2
Range	All	All	All	All	All	All

☒ Available⁽¹⁾
☐ Not available.
 ☐ Ask the commercial department.

⁽¹⁾Some option combinations may not be possible.

Technical features



Sheet metal



Small vision



Big vision

GENERAL FEATURES




Total weight	Reference: T1 PL800 mm HL 2000 mm with vision panels - 70 kg
Self closing system	Spring Optional : DITEC (button actuated system)

INSTALLATION

Pre-adjusted and tested to simplify the installation.


Technical drawing

CLASSIC






CO	500	550	600	650	700	750	800	850	900	1000
A	157	157	157	157	182	182	207	207	232	257

CLASSIC blind





Technical drawing

C310 "Luxury"




Technical drawing

M310 "Elegance"





Σημείωση / Note



Technical drawing




C520 "BIG VISION"



CO	600	650	700	750	800	850	900	950	1000
A	385	385	485	485	585	585	685	685	785


Technical drawing

C710



CO	600	650	700	750	800	850	900	950	1000
A	385	385	485	485	585	585	685	685	785

Classic heavy duty

Semiautomatic



Sales contacts

General: commercial@klefer.com

www.klefer.com

Hellenic Business Registry No: 14504535000

Klefer reserves the right to make changes to the specification of the products within this catalogue without prior notice.